



Technical Data Sheet

DF5350-9001 Bernyl Surfacer White

This post catalyzed acid cured primer coat is extremely fast drying and curing. It has very high solids and excellent filling properties on MDF and other wood substrates. This product gives very good coverage and it builds up the surface extremely well. The primer has excellent sanding properties for interior furniture and fittings. You will get the best result if you use our full Matador-system:

Bernyl Transparent Surfacer, Bernyl Surfacer White and Matador. Its Formaldehyde emission meets the German E1 specification, Report no 90K1 0049:F Swedish National Testing and Research Institute. This product does not contain any ketones or methanol, nor any D.O.P. or D.B.P. plasticizers. This product has extremely low HAPs content.

Product Data:

Gloss:	n/a	Binders:	Alkyd, Amino, Cellulose Ester
Solvents:	Esters, Alcohols, Aromatics	VOC:	431 g/l
Solids by Wt.:	66%	Fire risk class:	Flammable
(Theoretical)			
Spec. Gravity:	1.28	Frost Sensitive:	No
Viscosity:	155-185 sec DIN 4	Working Temp.:	>18° C, substrate, coating and air
Shelf Life:	1 year (at 15-25° C). Stir well before use.		

Mixing/Application:

Method	Hardener	Amount (Parts by Vol.)	Thinner	Viscosity (sec. DIN 4)	Application Amount (g/m ²) (23° C)	Pot Life (23° C)
Spray	309/2750	12%	309/OC 140	22-25	100-140	1 day

The substrate should be well prepared prior to painting.

Sand the first coat (within 8 hours of topcoating) in order to eliminate grain raising, if any, and improve adhesion of the subsequent coat.

Drying/Curing:

Method	Drying Temp.	Drying Time (@ 60 % RH)
Air Drying	20 C	1-2 hours, sandable
Forced Drying		

2001/09/df5350-9001

For your safety:

Remember to read M.S.D.S.
Produce samples first!
Remember to stir the container!

Becker Acroma has very high quality coating systems which demand experienced and extremely careful application.

Contact your Becker Acroma Technical Service Representative if you have any questions.

CALGARY NORTH
Phone: (403) 295-9676
Fax: (403) 295-2260
Email odn@bellare.com

EDMONTON NORTH
Phone: (780) 471-6160
Fax: (780) 471-4828
Email ode@bellare.com

CALGARY SOUTH
Phone: (403) 640-0260
Fax: (403) 640-0410
Email ods@bellare.com

Points worth noting:

A perfect result depends on a number of factors: the nature of the substrate, the technical and physical possibilities, as well as the user's application technique.

Our suggestions are therefore merely recommendations and not binding. All deliveries are governed by the latest edition of the Becker Acroma Condition of Sales.